



C&C TIMBER MOISTURE METER ACCESSORIES



Sliding Hammer Electrode

Fitted with 60mm hardened steel needle probes with insulated shafts for taking gradient readings through a section of timber to a depth of 45mm.

Optional 45mm insulated needle probes will measure to a depth of 30mm

Dimensions 315mm long x 45mm dia.

Weight 1.5kg



Hammer Electrode CH101

Heavy duty electrode fitted with triangular hardened steel blades.

Used with a hammer like action this electrode is most suited for checking or selecting rough sawn timber stacked ready for use.

Dimensions 275mm long x 85mm.

Weight 711g



Calibration Test Card

For checking resistance type timber moisture meter calibration.

Simply place the electrode needles or blades across the test pads and compare the readings with those shown on the card.

Calibration Reference: AS/NZS 1080.1:1997

Dimensions 76 x 57 x 10mm

Weight 55g

CARREL & CARREL LTD

MANUFACTURERS, IMPORTERS AND DISTRIBUTORS OF ELECTRICAL ENGINEERING PRODUCTS
POSTAL ADDRESS: P O BOX 2102, AUCKLAND 1140, NEW ZEALAND
FACTORY AND OFFICE: 3 McDONALD STREET, MORNINGSIDA AUCKLAND
TELEPHONE: +64-9-846 9124 FACSIMILE: +64-9-846 8555
EMAIL: sales@ carrel.co.nz WEB: www.carrel.co.nz